

Outperform every day.

Project:

Item Number:

Quantity:

REFRIGERATED DISPLAY CASES INTERNATIONAL



Drop-in Case



Curved Case



Self-Service Curved Case



Cubed Case

DESCRIPTION

Vollrath's self-contained Refrigerated Display Cases keep chilled food refrigerated while it is displayed for sale. Drop-in cases have sliding operator side doors for easy access for selling, refilling, changing displays and end-of-day cleaning. Countertop cases are available with customer and operatorside access or operator-side-only access. Display cases are not intended for overnight storage of perishable food.

CLEARANCE REQUIREMENTS

- Drop-in cases require a minimum of 4" (10.2 cm) of noncombustible countertop to support the unit and a minimum of 6" (15.2 cm) clearance on all sides of the drop-in for proper air circulation.
- Countertop cases require a minimum of 4" (10.2 cm) between the equipment and any surrounding walls. Surrounding walls must be made of non-combustible materials.
- Drop-in case requires a minimum of 80 square inches for fresh air intake and a minimum of 80 square inches for exhaust. See back page for details.

Agency Listings



Du ww

> Vollrath Europe BV Beneluxbaan 7 5121 AD RIJEN The Netherlands +31161870005

Vollrath of China Vollrath Shanghai Trading Limited 23A, Time Square Plaza | 500 Zhang Yang Road Pudong, Shanghai 200122 Tel: 86-21-50589580

Vollrath de Mexico S. de R.L. de C.V. Periferico Sur No. 7980 Edificio 4-E Col. Santa Maria Tequepexpan 45600 Tlaquepaque, Jalisco | Mexico Tel: (52) 333-133-6767 Tel: (52) 333-133-6769

Date

Fax: (52) 333-133-6768

ITEMS

Item No.	Model No.	Description
4084205	RDE1136	Drop-in Case, 36"
4084305	RDE1148	Drop-in Case, 48"
4084405	RDE1160	Drop-in Case, 60"
4085205	RDE1236	Countertop Curved Case, 36"
4085305	RDE1248	Countertop Curved Case, 48"
4085405	RDE1260	Countertop Curved Case, 60"
4086205	RDE1336	Countertop Cubed Case, 36"
4086305	RDE1348	Countertop Cubed Case, 48"
4086405	RDE1360	Countertop Cubed Case, 60"
4088005	RDE1436	Self-Serve Curved Case, 36"
4088105	RDE1448	Self-Serve Curved Case, 48"
4088205	RDE1460	Self-Serve Curved Case, 60"
4088605	RDE1536	Self-Serve Cubed Case, 36"
4088705	RDE1548	Self-Serve Cubed Case, 48"
4088905	RDE1560	Self-Serve Cubed Case, 60"

FEATURES

- Inside lighting strips located both at the top of the case and underneath the upper shelf create optimum food display throughout cabinet
- Self-contained refrigeration system
- Dual fans circulate air throughout the case to ensure even temperature control
- Double-glazed front glass gives added strength and insulation
- Case defrost mode
- Countertop cases with only operator-side access have a glass heater feature. Not available on drop-in cases or cases with customer-side (self serve) access.
- Drop-in and curved cases have one floating shelf. The cubed case has 2 floating shelves.
- Lift-and-remove rear sliding doors for easy display changes and end of day cleaning
- Drop-in cases can also be used as freestanding countertop units
- 32° 68°F (0° 20°C) temperature range
- 6 ft. (1.8 m) cord
- Display case has IEC inlet. Ships with three electrical cords, one each with UK, Schuko, or China plug
- Note: these items must ship by truck

WARRANTY

Approvals

All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to www.Vollrath.com.

e to continued product improvement, please consult w.vollrath.com for current product specifications.	


The Vollrath Company, L.L.C. Headquarters 1236 North 18th Street Sheboygan, Wisconsin 53081-3201 USA Main Tel: 800-624-2051 or 920-457-4851


Main Fax: 800-752-5620 or 920-459-6573 Canada Customer Service: 800-695-8560 Tech Services: techservicereps@vollrathco.com www.vollrath.com

INTERNATIONAL REFRIGERATED DISPLAY CASES

DIMENSIONS (Shown in inches (cm))

Drop-in Display Cases






Customer Side View


Drop-in Venting Requirements

Customer supplied louvers must be installed in surrounding cabinet to ensure adequate ventilation. One intake and one discharge louver are required. Preferred louver location is the short ends of the cabinet.




Cutout, Clearance and Venting **Cubed Display Cases**

Curved Display Cases



Customer Side View



Customer Side View

SPECIFICATIONS

01 201	OI LOW TOATTONG																	
Item No.	Description	(A) Width	(B) Cutout Width		Amps	Watts	HР		Weight Ib (kg)		Description	(A) Width	Volts	Amps	Watts	HP	Hz	Weight Ib (kg)
4084205	-	36 (91.4)	34 (86.3)		2.2	358	3/8		210 (95.3)	4088005		35 ³ / ₈ (89.9)		3.4	427	1/4		190 (86.2)
4084305	Drop-in	48 (121.9)	45 (114.3)	220-240	2.8	442	1/2	50/60	250 (113.4)	AHXX III5	Self-Serve Curved	47¼ (120)	220-240	5.2	518	1/3	50/60	235 (106.6)
4084405		60 (152)	58 (147.3)		2.8	454	1 1		274 (124.3)	4088205		59 (149.9)		5.4	530	73		271 (122.9)
4085205		35 ⁷ / ₁₆ (90)			2.6	416	3/8		190 (86.2)	4088605		35% (89.9)		3.9	485	3/8		230 (104.3)
4085305	Countertop Curved	47¼ (120)	_	220-240	3.1	501	- ½	50/60	235 (106.6)	4088705	Cubea	47¼ (120)	220-240	4.8	598	6 1/3		281 (127.5)
4085405		59 (149.9)			3.3	532			271 (122.9)	4088905		59 (149.9)		5.0	626			322 (146)
4086205		35% (89.9)			2.8	456	3/8		230 (104.3)		case has II h with UK,					elec	trical	cords,
4086305	Countertop Cubed	47¼ (120)	_	220-240	3.3	562	1/2	50/60	281 (127.5)									
4086405		59 (149.9)			3.7	607			322 (146)									

The Vollrath Company, L.L.C. Headquarters 1236 North 18th Street Sheboygan, Wisconsin 53081-3201 USA Main Tel: 800-624-2051 or 920-457-4851 Main Fax: 800-752-5620 or 920-459-6573 Canada Customer Service: 800-695-8560 Tech Services: techservicereps@vollrathco.com www.vollrath.com

Vollrath Europe BV Beneluxbaan 7 5121 AD RIJEN The Netherlands +31161870005

Vollrath of China Vollrath Shanghai Trading Limited 23A, Time Square Plaza | 500 Zhang Yang Road Pudong, Shanghai 200122 Tel: 86-21-50589580

Vollrath de Mexico S. de R.L. de C.V. Periferico Sur No. 7980 Edificio 4-E Col. Santa Maria Tequepexpan 45600 Tlaquepaque, Jalisco | Mexico Tel: (52) 333-133-6767 Tel: (52) 333-133-6769 Fax: (52) 333-133-6768